

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : REVOLT
 Product code : 89167-75-89391

1.2. Recommended use and restrictions on use

1.3. Supplier

INNICTIS® CROP CARE, LLC
 1880 Fall River Drive, Suite 100
 Loveland, CO 80538
 T 855-466-8428

1.4. Emergency telephone number

Emergency number : ChemTrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Carcinogenicity, Category 2	H351 Suspected of causing cancer.
Specific target organ toxicity — Repeated exposure, Category 2	H373 May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment — Acute Hazard, Category 1	H400 Very toxic to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 1	H410 Very toxic to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labelling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

H351 - Suspected of causing cancer.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H400 - Very toxic to aquatic life.
 H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (GHS US) :

P201 - Obtain special instructions before use.
 P202 - Do not handle until all safety precautions have been read and understood.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P308+P313 - If exposed or concerned: Get medical attention
 P314 - Get medical advice/attention if you feel unwell.
 P391 - Collect spillage.
 P405 - Store locked up.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Rimsulfuron	(CAS-No.) 122931-48-0	25	Not classified
Sodium Lignosulfonate	(CAS-No.) 8061-51-6	6	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335 STOT RE 2, H373
titanium(IV) oxide	(CAS-No.) 13463-67-7	1	Carc. 2, H351

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Wash skin with plenty of water.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Specific hazards arising from the chemical

- Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area. Do not breathe dust/fume/gas/mist/vapours/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Collect spillage.
Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Do not breathe dust/fume/gas/mist/vapours/spray.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

REVOLT	
No additional information available	
Rimsulfuron (122931-48-0)	
No additional information available	
Sodium Lignosulfonate (8061-51-6)	
No additional information available	
titanium(IV) oxide (13463-67-7)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH TWA (mg/m ³)	10 mg/m ³

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Granules.
- Colour : Mixture contains one or more component(s) which have the following colour(s):
Yellow-brown to dark brown Pure substance: white Unpurified: coloured
- Odour : mild
- Odour threshold : No data available

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

pH	: 6.7
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Relative evaporation rate (butylacetate=1)	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive limits	: Not applicable
Explosive properties	: No data available
Oxidising properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

REVOLT	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 inhalation rat (mg/l)	> 5 mg/l/4h
Sodium Lignosulfonate (8061-51-6)	
LD50 oral rat	> 40000 mg/kg (Rat)
titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg (Rat; OECD 425: Acute Oral Toxicity: Up-and-Down Procedure; Experimental value; > 5000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	> 10000 mg/kg (Rabbit; Experimental value)

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

titanium(IV) oxide (13463-67-7)	
LC50 inhalation rat (mg/l)	> 6.8 mg/l/4h (Rat; Experimental value)
Skin corrosion/irritation	: Not classified pH: 6.7
Serious eye damage/irritation	: Not classified pH: 6.7
Respiratory or skin sensitisation	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

REVOLT	
IARC group	2B - Possibly carcinogenic to humans

titanium(IV) oxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified

Sodium Lignosulfonate (8061-51-6)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Sodium Lignosulfonate (8061-51-6)	
STOT-repeated exposure	May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life with long lasting effects.

REVOLT	
LC50 fish 1	390 mg/l Rainbow Trout: (96h LC50)
LC50 other aquatic organisms 1	1.6 mg/l Green Algae (120h EC50)
EC50 Daphnia 1	360 mg/l
LC50 fish 2	390 mg/l Bluegill sunfish: (96h LC50)
NOEC (acute)	110 mg/l Rainbow Trout (90d NOEC)

Sodium Lignosulfonate (8061-51-6)	
LC50 fish 1	7300 mg/l 48 h; Salmo gairdneri (Oncorhynchus mykiss)

titanium(IV) oxide (13463-67-7)	
LC50 fish 1	> 1000 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	< 1000 mg/l (432 h; Daphnia magna; Static system)
LC50 fish 2	> 1 g/l (96 h; Leuciscus idus)
EC50 Daphnia 2	< 500 mg/l (720 h; Daphnia magna; Static system)
Threshold limit algae 1	61 mg/l (72 h; Pseudokirchneriella subcapitata)

12.2. Persistence and degradability

Sodium Lignosulfonate (8061-51-6)	
Persistence and degradability	Not readily biodegradable in water. Not established.

titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable. Low potential for mobility in soil.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

titanium(IV) oxide (13463-67-7)	
ThOD	Not applicable
BOD (% of ThOD)	Not applicable

12.3. Bioaccumulative potential

Sodium Lignosulfonate (8061-51-6)	
Partition coefficient n-octanol/water (Log Pow)	-3.45 (Estimated value)
Bioaccumulative potential	Bioaccumulation: not applicable. Not established.

titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3077 Environmentally hazardous substances, solid, n.o.s. (CONTAINS RIMSULFURON), 9, III
UN-No.(DOT) : UN3077
Proper Shipping Name (DOT) : Environmentally hazardous substances, solid, n.o.s. (CONTAINS RIMSULFURON)
Class (DOT) : 9 - Class 9 - Miscellaneous hazardous material 49 CFR 173.140
Packing group (DOT) : III - Minor Danger
Hazard labels (DOT) : 9 - Class 9 (Miscellaneous dangerous materials)



Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 213
DOT Packaging Bulk (49 CFR 173.xxx) : 240
DOT Symbols : G - Identifies PSN requiring a technical name

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- DOT Special Provisions (49 CFR 172.102) : 8 - A hazardous substance that is not a hazardous waste may be shipped under the shipping description "Other regulated substances, liquid or solid, n.o.s.", as appropriate. In addition, for solid materials, special provision B54 applies.
- 146 - This description may be used for a material that poses a hazard to the environment but does not meet the definition for a hazardous waste or a hazardous substance, as defined in 171.8 of this subchapter, or any hazard class as defined in Part 173 of this subchapter, if it is designated as environmentally hazardous by the Competent Authority of the country of origin, transit or destination.
- 335 - Mixtures of solids that are not subject to this subchapter and environmentally hazardous liquids or solids may be classified as "Environmentally hazardous substances, solid, n.o.s.," UN3077 and may be transported under this entry, provided there is no free liquid visible at the time the material is loaded or at the time the packaging or transport unit is closed. Each transport unit must be leakproof when used as bulk packaging.
- 384 - For transportation by motor vehicle, substances meeting the conditions for high viscosity flammable liquids as prescribed in §173.121(b)(1)(i), (b)(1)(ii), and (b)(1)(iv) of this subchapter, may be reassigned to Packing Group III under the following conditions:
- A112 - Notwithstanding the quantity limits shown in Column (9A) and (9B) for this entry, the following IBCs are authorized for transportation aboard passenger and cargo-only aircraft. Each IBC may not exceed a maximum net quantity of 1,000 kg:
- a. Metal: 11A, 11B, 11N, 21A, 21B and 21N
 - b. Rigid plastics: 11H1, 11H2, 21H1 and 21H2
 - c. Composite with plastic inner receptacle: 11HZ1, 11HZ2, 21HZ1 and 21HZ2
 - d. Fiberboard: 11G
 - e. Wooden: 11C, 11D and 11F (with inner liners)
 - f. Flexible: 13H2, 13H3, 13H4, 13H5, 13L2, 13L3, 13L4, 13M1 and 13M2 (flexible IBCs must be sift-proof and water resistant or must be fitted with a sift-proof and water resistant liner).
- B54 - Open-top, sift-proof rail cars are also authorized.
- B120 - The use of flexible bulk containers conforming to the requirements in subpart R and subpart S of part 178 of this subchapter is permitted.
- IB8 - Authorized IBCs: Metal (11A, 11B, 11N, 21A, 21B, 21N, 31A, 31B and 31N); Rigid plastics (11H1, 11H2, 21H1, 21H2, 31H1 and 31H2); Composite (11HZ1, 11HZ2, 21HZ1, 21HZ2, 31HZ1 and 31HZ2); Fiberboard (11G); Wooden (11C, 11D and 11F); Flexible (13H1, 13H2, 13H3, 13H4, 13H5, 13L1, 13L2, 13L3, 13L4, 13M1 or 13M2).
- IP3 - Flexible IBCs must be sift-proof and water-resistant or must be fitted with a sift-proof and water-resistant liner.
- N20 - A 5M1 multi-wall paper bag is authorized if transported in a closed transport vehicle.
- N91 - The use of a non specification sift-proof, non-bulk, metal can with or without lid, or a non specification sift-proof, non-bulk fiber drum, with or without lid is authorized when transporting coal tar pitch compounds by motor vehicle or rail freight. The fiber drum must be fabricated with a three ply wall, as a minimum. The coal tar pitch compound must be in a solid mass during transportation.
- T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2)
- TP33 - The portable tank instruction assigned for this substance applies for granular and powdered solids and for solids which are filled and discharged at temperatures above their melting point which are cooled and transported as a solid mass. Solid substances transported or offered for transport above their melting point are authorized for transportation in portable tanks conforming to the provisions of portable tank instruction T4 for solid substances of packing group III or T7 for solid substances of packing group II, unless a tank with more stringent requirements for minimum shell thickness, maximum allowable working pressure, pressure-relief devices or bottom outlets are assigned in which case the more stringent tank instruction and special provisions shall apply. Filling limits must be in accordance with portable tank special provision TP3. Solids meeting the definition of an elevated temperature material must be transported in accordance with the applicable requirements of this subchapter.
- DOT Packaging Exceptions (49 CFR 173.xxx) : 155
- DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : No limit
- DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : No limit
- DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
- Emergency Response Guide (ERG) Number : 171
- Other information : No supplementary information available.

Transportation of Dangerous Goods

- Transport document description : UN3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S., 9, III
- UN-No. (TDG) : UN3077

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Proper Shipping Name (Transportation of Dangerous Goods)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
TDG Primary Hazard Classes	: 9 - Class 9 - Miscellaneous Products, Substances or Organisms
Packing group	: III - Minor Danger
TDG Special Provisions	: 16 - (1) The technical name of at least one of the most dangerous substances that predominantly contributes to the hazard or hazards posed by the dangerous goods must be shown, in parentheses, on the shipping document following the shipping name in accordance with clause 3.5(1)(c)(ii)(A) of Part 3 (Documentation). The technical name must also be shown, in parentheses, on a small means of containment or on a tag following the shipping name in accordance with subsections 4.11(2) and (3) of Part 4 (Dangerous Goods Safety Marks). (2) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a shipping document or on a small means of containment when Canadian law for domestic transport or an international convention for international transport prohibits the disclosure of the technical name: (a)UN1544, ALKALOID SALTS, SOLID, N.O.S. or ALKALOIDS, SOLID, N.O.S.; (b)UN1851, MEDICINE, LIQUID, TOXIC, N.O.S.; (c)UN3140, ALKALOID SALTS, LIQUID, N.O.S. or ALKALOIDS, LIQUID, N.O.S.; (d)UN3248, MEDICINE, LIQUID, FLAMMABLE, TOXIC, N.O.S; or (e)UN3249, MEDICINE, SOLID, TOXIC, N.O.S. An example in Canada is the "Food and Drugs Act". (3) Despite subsection (1), the technical name for the following dangerous goods is not required to be shown on a small means of containment: (a)UN2814, INFECTIOUS SUBSTANCE, AFFECTING HUMANS; or (b)UN2900, INFECTIOUS SUBSTANCE, AFFECTING ANIMALS. SOR/2014-306,99 - (1)Mixtures of solids that are not dangerous goods and liquids or solids that are UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, may be handled, offered for transport or transported as UN3077 if there is no visible liquid when the dangerous goods are loaded into a means containment and during transport. (2)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of less than 450 kg of UN3077, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S, or less than 450 L of UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S, on a road vehicle or a railway vehicle. The dangerous goods must be contained in one or more small means of containment designed, constructed, filled, closed, secured and maintained so that under normal conditions of transport, including handling, there will be no accidental release of the dangerous goods that could endanger public safety. SOR/2014-306
Explosive Limit and Limited Quantity Index	: 5 kg

Transport by sea

Transport document description (IMDG)	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. ((CONTAINS RIMSULFURON)), 9, III
UN-No. (IMDG)	: 3077
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S.
Class (IMDG)	: 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG)	: III - substances presenting low danger
Limited quantities (IMDG)	: 5 kg
Marine pollutant	: Yes



Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

REVOLT

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Rimsulfuron	CAS-No. 122931-48-0	25%
-------------	---------------------	-----

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Sodium Lignosulfonate (8061-51-6)	
EPA Labeling Requirements	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
FIFRA Labelling	
EPA Registration Number	89167-75-89391
This chemical is a pesticide product registered by the Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets, and for workplace labels of non-pesticide chemicals. Following is the hazard information as required on the pesticide label.	
FIFRA Signal Word	Caution
FIFRA Precautionary Statement	Call a doctor if you feel unwell. Keep out of reach of children.
FIFRA Human Health Hazards	CAUTION: Harmful if swallowed. Harmful if absorbed through skin. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.
FIFRA First Aid	If swallowed: • Call a poison control center or doctor immediately for treatment advice. Have a person sip a glass of water if able to swallow. • DO NOT induce vomiting unless told to do so by a poison control center or doctor. • DO NOT give anything to an unconscious person. If on skin: • Take off contaminated clothing. • Rinse skin with plenty of water for 15 to 20 minutes. • Call a poison control center or doctor for treatment advice.
FIFRA Environmental Hazards	DO NOT apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. DO NOT contaminate water when cleaning equipment or disposing of equipment washwaters or rinsate.

15.2. International regulations

CANADA

Rimsulfuron (122931-48-0)	
Not listed on the Canadian DSL (Domestic Substances List)/NDSL (Non-Domestic Substances List)	
Sodium Lignosulfonate (8061-51-6)	
Listed on the Canadian DSL (Domestic Substances List)	
titanium(IV) oxide (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List)	

EU-Regulations

No additional information available

National regulations

REVOLT	
This chemical is a pesticide product registered by the United States Environmental Protection Agency and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use. PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS CAUTION: Causes moderate eye irritation. Harmful if inhaled. Avoid contact with eyes or clothing. Avoid breathing dust. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or frequent repeated skin contact while handling the material may cause allergic reaction in some individuals.	
titanium(IV) oxide (13463-67-7)	
Listed on IARC (International Agency for Research on Cancer)	

15.3. US State regulations

California Proposition 65 - This product can expose you to chemicals including titanium dioxide, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

Component	State or local regulations
titanium(IV) oxide(13463-67-7)	U.S. - Massachusetts - Right To Know List; U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

REVOLT

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-statements:

H315	Causes skin irritation.
H320	Causes eye irritation
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.